

CaseHistory

FLOOR COATING
10-12 mils thick (1) coat
Returned to service in
15 hours

PROJECT:

Floor Coating - circuit board
assembly area.

OWNER:

Mid-west area manufacturing
company (classified)

INSTALLER:

McCormick Enterprises

SYSTEM:

POLYPRO™ 6058
Color: light gray

AREA:

12,000 sq. ft.

COMPLETED:

2000



POLYPRO™
One Component (2K)

POLYPRO™ Exploration

DISCUSSION: Quick turn-around, high reflectivity, high quality, durability and excellent cleanability were the primary requirements by this computer component manufacturing company for re-coating their production area floor. Their delivery requirements necessitated a full seven day production schedule. The existing floor coating was badly deteriorated and severely in need of replacement.

The owner reluctantly shut down Friday at 1800 hours with assurance from the contractor that they would be back up by the following Monday morning.

The preparation and coating operations were completed by 0300 hours Sunday morning. Plant maintenance personnel were on the coating at 1800 hours Sunday. They applied three buffed-in coats of static releasing floor wax, replaced all equipment and turned the operations over to production Monday A.M.

PREPARATION AND COATING:

- Mop existing coating
- Squeegee 6058
- Abrade - # 60 grit disks
- Back roll 10-12 mils thick
- Porcupine roll to release air
- Re-clean
- Lap Prep tm for Adhesion



900 McFarland 400 Blvd. | Alpharetta, GA 30004
770.495.9554 (tel) 404.521.4396 (fax) | visuron@hansonco.net



VISURON
TECHNOLOGIES, INC.™